


Sirocco 1400 is a mid size laminator that covers the most common finishing requirements with high quality results.

Temperature control



Pressure sensitive films :

- Lamination, encapsulation, adhesive setting, mounting
- *40°C (104°F) recommended temperature for optimised results with cold films

Thermal films :


- Lamination & encapsulation with films up to 250 microns thickness (10 mil)
- Encapsulation with opaque backing substrates
- Use of different type of film (finishing or texture) on top & bottom
- ** Same temperature adjustment for the upper and lower heating rollers

This user friendly system can be operated even by operators without technical skills.





Optional electrical rewinding system to handle demanding job runs.



Creative applications with Sirocco 1400

SIROCCO 1400

Technical Specifications

Max. working width	1400 mm (55")
Width of the roller	1542 mm (60")
Diameter of the heating rollers	78 mm (3 1/16")
Max. thickness of print + board	25 mm (1")
Max. thickness of the film	250 microns / side (10 mil)
Adjustment and display of the roller temperature	yes, from 40 to 160°C 104 to 320°F
Digital display of the roller pressure	yes
Upper & lower winding and unwinding spindles	yes
Number of spindles delivered with the machine	4
Max. speed meter/min - (ft/min)	3 - (10)
Reverse operation	yes
Motor control pedal	yes
Emergency stop button	2
Stand mounted on self-locking castors	yes
Electrical print rewinding system	Optional
Power of the motor (W)	100
Heating power (W)	3400
Voltage	230V / 50Hz - 60 Hz single phase
Amperes	16 amps
Size of the machine	L 187x D 76x H 137cm - (74" x 30" x 54")
Weight of the machine kg - (Lbs)	287 - (632)
Size of the shipping crate	L 225x D 105x H 100 cm - (89"x42" x40")
Shipping weight kg - (Lbs)	335 - (737)
Made in France	
EC Certification	




KALA SAS - Parc de l'Ecotay
35 410 Nouvoitou - France

Tel. : +33 (0)2 99 37 64 64 - Fax : +33 (0)2 99 37 64 65
Internet : www.kala.fr - e-mail : info@kala.fr

Sirocco 1080 is an entry level laminator that can handle demanding job runs. Its performance surpasses the requirements of Printers & Finishers offering standard lamination services within a reasonable budget.

Temperature control

Upper roller
Lower roller



Pressure sensitive films :

- Lamination, adhesive setting and mounting

* 40°C (104°F) recommended temperature for optimised results with these laminating films

Thermal films :

- Encapsulation with lamination films up to 125 microns thickness (5 mil)
- Encapsulation with opaque backing substrates
- Use of different type of film (finishing or texture) on top and bottom position

** Same temperature adjustment for the top and bottom heating rollers

Sirocco 1080 fits into any office environment. Used as a table top laminator, it can be installed on a mobile stand, on castors with a storage space for film reels (optional).



This compact, economic and ergonomic system is extremely user friendly and can be used even by operators without technical skills.




SIROCCO 1080

Technical Specifications

Max. working width	1080 mm (42.5")
Length of the roller	1130 mm (44.5")
Diameter of the heating rollers	54 mm (2.1")
Max. thickness of print + board	25 mm (1")
Max. thickness of the film	125 microns / side - (5 mil)
Digital display of the roller temperature	yes, from 40 to 160°C (104 to 320°F)
Digital display of the roller pressure	yes
Upper winding and unwinding spindles, lower unwinding	yes
Number of spindles delivered with the machine	3
Max. speed meter/min - (ft/min)	3 - (10)
Reverse operation	yes
Motor control pedal	yes
Emergency stop button	2
Stand mounted on self-locking castors	optional
Electrical print rewinding system	optional
Power of the motor (W)	100
Heating power (W)	2800
Voltage	230V / 50Hz - 60 Hz single phase
Amperes	13 amps
Size of the machine (without stand)	L142 x D62 x H58 cm - (56"x25"x20")
Size of the stand	L142 x D76 x H68 cm - (56"x30"x27")
Weight of the machine without stand kg - (Lbs)	122 - (269)
Weight of the stand kg - (Lbs)	42 - (93)
Size of the shipping crate	L180 x D105 x H 100 cm - (71"x42"x40")
Shipping weight kg - (Lbs)	209 - (460)
Made in France - EC Certification	

Creative applications with Sirocco 1080



KALA SAS - Parc de l'Ecotay
35 410 Nouvoitou - France

Tel. : +33 (0)2 99 37 64 64 - Fax : +33 (0)2 99 37 64 65
Internet : www.kala.fr - e-mail : info@kala.fr